

» KISS 4U Q57 «



4U Open Solution

- » Long term available
- » I3, I5, I7 processors
- » Up to 8 GB DDR3
- » KISS Stor 1/0/5, KISS DAxxx

KISS 4U Q57

4U Kontron Industrial Silent Server

The KISS system has been designed with flexibility in mind and can accommodate PICMG 1.0, PICMG 1.3, ATX and Dual Xeon/64-bit based motherboards, as well as PCI Express ATX motherboards, all in a case that can be used as a tower, desktop or 19" rack mounted chassis. The main attraction of KISS servers is their extremely low noise level: they are inaudible against normal conversation. KISS IPC servers are therefore ideal for most noise-sensitive environments, such as hospital operating theaters and computer server rooms.

The performance and configuration of KISS servers are based on Kontron's extensive range of CPU boards and backplanes, which allows them to be adapted to meet a very wide range of requirements. Redundant PSUs, RAID Subsystem KISS Stor and Remote Diagnostic Software make KISS family a high reliable and contiguous operating industrial Server. Extra accessories adapt KISS to precisely meet your specific requirements.

Technical Information

System	KISS 4U Q57
Product Line	KISS 4U V2
Dimension (H x W x D)	177 mm x 482 mm x 472 mm 4U x 19" x 18,58"
Weight	Approx. 15 kg
Interfaces Front	2 x USB 2.0
Interfaces of the installed board (rear)	8 x USB 2.0 , 2 x GB LAN,PS/2 M+K , 3 x RS232, 1 x RS485 , 1 x VGA, Audio
Controls on frontside	ATX Switch
External accessible drive bays	3 x 5,25", 1 x 3,5", 1 x SLIM line
Internal drive bays	1 x 3.5"
Power supply	100-240 V AC 400 W (80+) optional AC 650 W (80+), AC Redundant 500 W
Expansion slots	1 PCI Express 2.0 x16 slot 1 PCI Express 2.0 x4 slot 2 PCI Express 2.0 x1 slots 3 PCI 2.3 33MHz slots
Memory	Up to 16GB system memory DDR3 1066/1333MHz
Processor	i3-540 3,06GHz i5-660 3,33GHz i7-860 2,8GHz
Temperature	
non-operating	-20°C to 70°C (-4°F to 158°F)
operating	0°C to 50°C (32°F to 122°F) 55°C (131°F) at 10% POH per month
Humidity	
non-operating	10-90% rel. humidity, non condensing
operating	10-95 % rel. humidity, non condensing
Shock	
non-operating	30g, 11ms
operating	15g, 11ms
Vibration	
operating	1g 10-500 Hz
storage	2g 10-500 Hz
Noise	35 dBA ~40 dBA for redundant PSU
Approvals	CE, desigend to meet UL
MTBF	50,000 h
Protection Class	Front: IP 20 optional IP 54
Options	DVD R/W KISS Stor Slide Rails PCCM KISS DAX

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany
Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building,Block #1,ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China
Tel.: + 86 10 63751188
Fax: + 86 10 83682438
info@kontron.cn

